

5

1. Field of the Invention

15

20

25

30

This white balance shift problem occurs due to changes in the number of emissions or the intensity of

Namely, phosphors of the three primary colors, red, green, and blue saturate in luminance as the number of emissions increases. This is because the persistence characteristics of the red, green, and blue phosphors, in other words, the energy conversion efficiency of the phosphors for excitation by ultraviolet radiation, decreases as the number of emissions increases. If white balance is adjusted at a specific point (A) where the number of emissions is large, the white balance value at that time is determined based on the luminance ratio among red, green, and blue at the specific point. On the other hand, when displaying an image in accordance with high APL video signals, the number of emissions is reduced in order to hold the power consumption within a predetermined value.

Accordingly, at another point (B) where the number of emissions is small, the energy conversion efficiency of the phosphors for excitation by ultraviolet radiation increases. If the rate of decrease of the energy conversion efficiency increases in the order of green, red, and blue, then the luminance increases relative to that at the specific point, in the order of green, red, and blue. That is, there is a difference in white balance between the specific point (A) and another point (B) because the luminance ratio among red, green, and blue at the other point (B) differs from the value

used for adjustment at the specific point (A).

Conversely, when displaying an image in accordance with video signals whose APL is lower than that when the white balance was adjusted, the number of
5 emissions may be increased, resulting in a further decrease in the energy conversion efficiency, and causing a difference in white balance because the luminance ratio among red, green, and blue changes, as in the case where the number of emissions is decreased.

10 The prior art and the problem associated with the prior art will be described in detail later with reference to accompanying drawings.

Though the present invention can be applied not only to plasma display apparatuses but also to various
15 other display apparatuses such as display apparatuses using EL elements, FEDs, and CRTs, the following description will be given by dealing primarily with a plasma display apparatus as an example of a display apparatus that uses phosphors of three primary colors,
20 red, green, and blue, whose persistence characteristics differ from one another.

SUMMARY OF THE INVENTION

An object of the present invention is to provide a white balance correction circuit and correction method,
25 for a display apparatus, capable of maintaining correct white balance regardless of the number of emissions or the intensity of emission.

According to the present invention, there is provided a display apparatus for displaying a color image
30 by controlling the number of emissions or the intensity thereof in accordance with primary color video signals input thereto, comprising a detection portion detecting the number of emissions or the intensity; and a white balance correction portion correcting white balance by
35 adjusting the amplitudes of the primary color video signals in accordance with the detected number of emissions or the detected intensity.

09722621.12800

0972661 11300

The detection portion may detect the number of emissions or the intensity from a display ratio of an image produced by the primary color video signals. The display apparatus may further comprise a control portion
5 controlling the number of emissions for, or the intensities of, the primary color video signals in accordance with the display ratio of the image. The white balance correction portion may comprise a computing unit and a plurality of multipliers wherein the computing
10 unit may compute amplitude coefficients for the primary color video signals in accordance with the display ratio of the image, and the multipliers may multiply the primary color video signals respectively by the computed amplitude coefficients.

15 The white balance correction portion may comprise a storage unit and a plurality of multipliers wherein the storage unit may output amplitude coefficients for the primary color video signals in accordance with the display ratio of the image, and the multipliers may
20 multiply the primary color video signals respectively by the amplitude coefficients output from the storage unit. The white balance correction portion may comprise a storage unit wherein the storage unit may output amplitude-adjusted primary color video signals in
25 accordance with the primary color video signals and the display ratio of the image.

The detection portion may detect the number of emissions or the intensity from a display current that flows when displaying an image in accordance with the
30 primary color video signals. The display apparatus may further comprise a control portion controlling the number of emissions for, or the intensities of, the primary color video signals in accordance with the image display current. The white balance correction portion may
35 comprise a computing unit and a plurality of multipliers wherein the computing unit may compute amplitude coefficients for the primary color video signals in

storage unit wherein the storage unit may output
amplitude-adjusted primary color video signals in
accordance with the primary color video signals and the
externally applied luminance-adjusting input. Emissions
5 due to the primary color video signals may be produced
from phosphors of three primary colors, red, green, and
blue. The display apparatus may be a plasma display
apparatus.

According to the present invention, there is also
10 provided a display apparatus for displaying a color image
by controlling the number of emissions or the intensity
thereof in accordance with primary color video signals
input thereto, wherein output gray levels of images
represented by the primary color video signals are
15 adjusted in accordance with input gray levels of the
images represented by the primary color video signals,
thereby correcting white balance which varies with the
number of emissions for, or the intensities of, the
primary color video signals.

The display apparatus may further comprise a first
20 detection portion detecting the input gray levels of the
images represented by the primary color video signals;
and a correction portion correcting the white balance by
adjusting the output gray levels of the primary color
25 video signals in accordance with the detected input gray
levels. The white balance correction portion may
comprise a computing unit and a plurality of correction
units wherein the computing unit may compute gray level
correction coefficients in accordance with the detected
30 input gray levels, and the correction units may apply
corrections to the input gray levels by using the
computed correction coefficients.

The white balance correction portion may comprise a
storage unit and a plurality of correction units wherein
35 the storage unit may output gray level correction
coefficients in accordance with the detected input gray
levels, and the correction units may apply corrections to

09722621 112300

the input gray levels by using the computed correction coefficients. The display apparatus may further comprise a second detection portion detecting a display ratio or display current of an image produced by the primary color video signals; and a control portion controlling the number of emissions for, or the intensities of, the primary color video signals in accordance with the detected display ratio or the detected display current.

Further, according to the present invention, there is provided a white balance correction circuit for use in a display apparatus which displays a color image by controlling the number of emissions or the intensity thereof in accordance with primary color video signals input thereto, and which includes a detection portion detecting the number of emissions or the intensity, wherein the white balance correction circuit corrects white balance by adjusting the amplitudes of the primary color video signals in accordance with the detected number of emissions or the detected intensity.

20 The white balance correction circuit may further
comprise a computing unit computing amplitude
coefficients for the primary color video signals in
accordance with the number of emissions or the intensity;
and a plurality of multipliers multiplying the primary
25 color video signals respectively by the computed
amplitude coefficients wherein the white balance, which
varies with the number of emissions for, or the
intensities of, the primary color video signals, may be
corrected by adjusting the amplitudes of the primary
30 color video signals in accordance with the controlled
number of emissions or the controlled intensity. The
white balance correction circuit may further comprise a
storage unit storing amplitude coefficients for the
primary color video signals, and outputting the amplitude
35 coefficients in accordance with the number of emissions
or the intensity; and a plurality of multipliers
multiplying the primary color video signals respectively

25

30

35

by the output amplitude coefficients wherein the white balance, which varies with the number of emissions for, or the intensities of, the primary color video signals, may be corrected by adjusting the amplitudes of the primary color video signals in accordance with the controlled number of emissions or the controlled intensity.

The white balance correction circuit may further comprise a computing unit computing amplitude coefficients for the primary color video signals in accordance with the number of emissions or the intensity; and wherein the white balance, which varies with the number of emissions for, or the intensities of, the primary color video signals, may be corrected by adjusting the amplitudes of the primary color video signals in accordance with the controlled number of emissions or the controlled intensity. The white balance correction circuit may further comprise a storage unit storing amplitude-adjusted primary color video signals, and outputting the amplitude coefficients in accordance with the primary color video signals and the number of emissions or the intensity; and wherein the white balance, which varies with the number of emissions for, or the intensities of, the primary color video signals, may be corrected by adjusting the amplitudes of the primary color video signals in accordance with the controlled number of emissions or the controlled intensity.

The detection portion may detect the number of emissions or the intensity from a display ratio of an image produced by the primary color video signals. The detection portion may detect the number of emissions or the intensity from a display current that flows when displaying an image in accordance with the primary color video signals. The detection portion may detect the number of emissions or the intensity from an externally applied luminance-adjusting input.

09720601 113000

In addition, according to the present invention, there is provided a white balance correction circuit for use in a display apparatus which displays a color image by controlling the number of emissions or the intensity thereof in accordance with primary color video signals input thereto, and which includes a detection portion detecting the number of emissions or the intensity, wherein output gray levels of images represented by the primary color video signals are adjusted in accordance with input gray levels of the images represented by the primary color video signals, thereby correcting white balance which varies with the number of emissions for, or the intensities of, the primary color video signals.

The white balance correction circuit may further comprise a first detection portion detecting the input gray levels of the images represented by the primary color video signals; and a correction portion correcting the white balance by adjusting the output gray levels of the primary color video signals in accordance with the detected input gray levels. The white balance correction circuit may further comprise a computing unit computing gray level correction coefficients in accordance with the detected input gray levels; and a plurality of correcting units for applying corrections to the input gray levels by using the computed correction coefficients. The white balance correction circuit may further comprising a storage unit outputting gray level correction coefficients in accordance with the detected input gray levels; and a plurality of correcting units for applying corrections to the input gray levels by using the output correction coefficients.

The white balance correction circuit may further comprise a second detection portion detecting a display ratio or display current of an image produced by the primary color video signals; and a control portion controlling the number of emissions for, or the intensities of, the primary color video signals in

accordance with the detected display ratio or the detected display current.

According to the present invention, there is provided a white balance correction method for a display apparatus which displays a color image by controlling luminance in accordance with primary color video signals input thereto, wherein an amplitude ratio between the primary color video signals is set in accordance with the luminances of the primary color video signals, thereby suppressing variation of white balance with the luminances.

Further, according to the present invention, there is provided a white balance correction method for a display apparatus which displays a color image by controlling the number of emissions or the intensity thereof in accordance with primary color video signals input thereto, wherein the number of emissions or the intensity is detected; and white balance is corrected by adjusting the amplitudes of the primary color video signals in accordance with the detected number of emissions or the intensity.

The number of emissions or the intensity may be detected from a display ratio of an image produced by the primary color video signals. The white balance correction method may further comprise the step of controlling the number of emissions for, or the intensities of, the primary color video signals in accordance with the display ratio of the image. The number of emissions or the intensity may be detected from a display current that flows when displaying an image in accordance with the primary color video signals. The white balance correction method may further comprise the step of controlling the number of emissions for, or the intensities of, the primary color video signals in accordance with the image display current.

The number of emissions or the intensity may be detected from an externally applied luminance-adjusting

09722621.1300

input. The white balance correction method may further
comprise the step of controlling the number of emissions
for, or the intensities of, the primary color video
signals in accordance with the externally applied
5 luminance-adjusting input.

In addition, according to the present invention,
there is provided a white balance correction method for a
display apparatus which displays a color image by
controlling the number of emissions or the intensity
10 thereof in accordance with primary color video signals
input thereto, wherein output gray levels of images
represented by the primary color video signals are
adjusted in accordance with input gray levels of the
images represented by the primary color video signals,
15 thereby correcting white balance which varies with the
number of emissions for, or the intensities of, the
primary color video signals.

The white balance correction method may further
comprise the steps of detecting the input gray levels of
20 the images represented by the primary color video
signals; and adjusting the output gray levels of the
primary color video signals in accordance with the
detected input gray levels. The white balance correction
method may further comprise the step of controlling the
25 number of emissions for, or the intensities of, the
primary color video signals in accordance with a display
ratio or display current of the image.

According to the present invention, there is
provided a white balance correction method for a display
30 apparatus which displays a color image by controlling
luminance in accordance with primary color video signals
input thereto, wherein an amplitude ratio between the
primary color video signals is set in accordance with the
luminances of the primary color video signals, thereby
35 suppressing variation of white balance with the
luminances.

The luminances of the primary color video signals

00821 "T2922760

may be defined by the number of emissions for, or the intensities of, the primary color video signals. A color image may be displayed by means of light-emitting elements in accordance with luminance-defined primary color video signals.

Further, according to the present invention, there is also provided a white balance correction circuit for use in a display apparatus which displays a color image using primary color video signals, comprising an adjusting unit adjusting the amplitude of each of the primary color video signals; a storage unit storing an amplitude ratios for correcting the amplitudes of the primary color video signals; and a setting unit setting in the adjusting unit amplitude ratios stored in the storage unit wherein the amplitude ratio between the primary color video signals is set in accordance with the number of emissions for, or the intensities of, the primary color video signals, thereby correcting white balance which varies with the number of emissions for, or the intensities of, the primary color video signals.

In addition, according to the present invention, there is provided a white balance correction circuit for use in a display apparatus which displays a color image using primary color video signals, comprising an adjusting unit adjusting the amplitude of each of the primary color video signals; a computing unit computing an amplitude ratio for each of the primary color video signals from the number of emissions for, or the intensities of, the primary color video signals; and a setting unit setting in the adjusting unit the amplitude ratio computed by the computing unit wherein the amplitude ratio between the primary color video signals is set in accordance with the number of emissions for, or the intensities of, the primary color video signals, thereby correcting white balance which varies with the number of emissions for, or the intensities of, the primary color video signals.

09732621 113800

BRIEF DESCRIPTION OF THE DRAWINGS

The present invention will be more clearly understood from the description of the preferred embodiments as set forth below with reference to the accompanying drawings, wherein:

Figure 1 is a block diagram schematically showing one example of a surface discharge AC-driven type plasma display apparatus;

Figure 2 is a diagram for explaining one example of a driving sequence in the plasma display apparatus of Figure 1;

Figures 3A, 3B, and 3C are diagrams for explaining the relationships between average picture level (APL), number of emissions, and power consumption in the plasma display apparatus of Figure 1;

Figure 4 is a block diagram showing one example of a prior art white balance adjusting circuit;

Figures 5A and 5B are diagrams showing the relationship between the number of emissions and luminance for phosphors of three primary colors, red, green, and blue;

Figure 6 is a block diagram showing a first embodiment of a white balance correction circuit according to the present invention;

Figure 7 is a diagram showing the luminance ratios of three primary color phosphors relative to the blue phosphor, plotted against the number of emissions;

Figure 8 is a diagram for explaining the multiplication coefficients for the three primary colors, red, green, and blue, used in the white balance correction circuit of Figure 6;

Figure 9 is a diagram showing the luminance ratios of the three primary color phosphors corrected by the white balance correction circuit of Figure 6, plotted against the number of emissions;

Figure 10 is a block diagram showing one example of an APL detection circuit in the white balance correction

as He-Xe or Ne-Xe. When a voltage is applied to its associated scan/sustain electrode 12 and sustain electrode 13, a discharge occurs, and ultraviolet rays are generated. Each discharge cell has a phosphor coating which glows in red, green, or blue, and the ultraviolet rays excite the phosphor to emit colored light corresponding to the color of the phosphor. By utilizing this light emission and selecting discharge cells of the desired colors in accordance with video signals, a color image can be displayed.

In accordance with the display ratio (or display current) of the image produced by the video signals (three primary color video signals R, G, and B), the drive control circuit 17 controls the number of emissions for the video signals via the scan/sustain pulse output circuit 15 and sustain pulse output circuit 16 so that power consumption does not exceed a predetermined value.

Figure 2 is a diagram for explaining one example of a driving sequence in the plasma display apparatus of Figure 1, that is, a time-division driving method (hereinafter referred to as the subfield method) utilizing the above-described emission principle.

The subfield method is a method that divides one frame into a plurality of subfields (SF1 to SF4) differently weighted according to the difference in the number of emissions, and reproduces a grayscale by selecting for each pixel a subfield appropriate to the signal amplitude representing the pixel.

The driving sequence based on the subfield method shown in Figure 2 shows an example in which one frame is divided into four subfields SF1 to SF4 to display 16 gray levels. Scan period T1 of each subfield is a period for selecting a discharge cell (hereinafter called a light-emitting cell) that emits light in the subfield, and discharge sustain period T2 is a period for the duration of which the selected light-emitting cell emits light.

The discharge sustain period T2 of each of the

003211 1292460

5 selecting an appropriate one of the subfields SF1 to SF4
in accordance with the video signal level, $2^4 = 16$ gray
levels can be reproduced. If it is desired to increase
the number of gray levels, the number of subfields is
increased; for example, if the number of subfields is
0 increased to 8, $2^8 = 256$ gray levels can be reproduced.
The luminance level of each subfield is controlled by the
number of sustain emissions (number of emissions).

number of emissions, and power consumption in the plasma display apparatus of Figure 1: Figure 3A shows the relationship between the number of emissions of a light-emitting cell and the power consumption, Figure 3B shows the relationship between the average picture level (APL) of an image (display panel) and the number of emissions, and Figure 3C shows the relationship between the average picture level of an image produced by video signals and the power consumption.

25 plasma display apparatus increases as the number of
emissions of the display cell increases. In view of
this, in practical plasma display apparatuses, when the
average picture level (APL) of an image is high, that is,
when displaying an image (video signals) such that the
30 light emission level is high over the entire screen,
control is performed to limit the power consumption
within a predetermined value, as shown in Figure 3C, by
limiting the number of emissions for the frame as a whole
while maintaining the weighting ratio defining the number
35 of emissions for each subfield.

That is, in Figure 3B, if the number of gray levels displayed is 256, then if the weighting ratio at point A

5

10

15

35



and the amplitudes of the respective color video signals R, G, and B are adjusted so that the desired white balance can be obtained. That is, white balance is adjusted for each set (plasma display apparatus), for example, prior to shipment from the factory; in that case, a prescribed adjustment pattern is displayed with a specified number of emissions and, in that state, the coefficients K_r , K_g , and K_b are stored in the registers in the microcomputer 2.

In the prior art white balance adjusting circuit, since the white balance is adjusted by displaying a prescribed adjustment pattern with a specified APL (that is, with a specified number of emissions), as described above, the white balance may become shifted when the number of emissions (APL) changes.

Figures 5A and 5B are diagrams showing the relationship between the number of emissions and luminance for the phosphors of three primary colors, red, green, and blue: Figure 5A shows the relationship between the number of emissions and luminance, and Figure 5B shows unit emission luminance characteristics due to the decrease of energy conversion efficiency.

As shown in Figure 5A, the phosphors of the three primary colors, red, green, and blue begin to saturate in luminance as the number of emissions increases. This is because the persistence characteristics of the red, green, and blue phosphors, in other words, the energy conversion efficiency of the phosphors for the excitation by ultraviolet radiation, decrease as the number of emissions increases, as shown in Figure 5B. In Figure 5B, the vertical axis represents the value of the luminance per unit emission normalized to the emission luminance per unit when the energy conversion efficiency is highest, and the horizontal axis represents the number of emissions.

Here, in Figures 5A and 5B, if white balance is adjusted at point A where the number of emissions is

large, the white balance value at that time is determined based on the luminance ratio among red, green, and blue at point A. On the other hand, when displaying an image in accordance with high APL video signals, the number of emissions is reduced in order to hold the power consumption within a predetermined value, as previously described.

Accordingly, at point B where the number of emissions is small, the energy conversion efficiency of the phosphors for the excitation by ultraviolet radiation increases as shown in Figure 5B; here, if the rate of decrease of the energy conversion efficiency increases in the order of green, red, and blue, then the luminance increases relative to that at point A, in the order of green, red, and blue. That is, there is a difference in white balance between point A and point B because the luminance ratio among red, green, and blue at point B differs from the value used for adjustment at point A.

Conversely, when displaying an image in accordance with video signals whose APL is lower than that when the white balance was adjusted, the number of emissions may be increased, resulting in a further decrease in the energy conversion efficiency, and causing a difference in white balance because the luminance ratio among red, green, and blue changes, as in the case where the number of emissions is decreased.

Specific embodiments of the white balance correction circuit, the correction method, and the display apparatus according to the present invention will now be described below with reference to drawings. In the description of the embodiments hereinafter given, a plasma display apparatus is taken as an example, but it will be appreciated that the present invention is applicable not only to plasma display apparatuses, but also to various other display apparatuses such as display apparatuses using EL elements, FEDs, LED displays, and CRTs.

Figure 6 is a block diagram showing a first

embodiment of the white balance correction circuit according to the present invention, and Figure 7 is a diagram showing the luminance ratios of three primary color phosphors relative to the blue phosphor, plotted against the number of emissions.

In Figure 6, reference numerals 11 to 13 are multipliers, 2 is a microcomputer, and 3 is an APL detection circuit (average picture level (display ratio) detection circuit). Reference characters Kr, Kg, and Kb are multiplication coefficients (amplitude coefficients) for the respective input video signals (three primary color digital video signals) R, G, and B.

As shown in Figure 6, the white balance adjusting circuit of the first embodiment adjusts the white balance by adjusting the amplitudes of the input video signals R, G, and B by means of the multipliers 11 to 13 using the multiplication coefficients Kr, Kg, and Kb supplied from the microcomputer 2. The microcomputer 2 sets the number of emissions based on the APL (average picture level, i.e., the display ratio) obtained from the APL detection circuit 3. Further, the microcomputer 2 computes from the number of emissions the rate of change of the luminance ratio of each of R, G, and B (red, green, and blue) due to the change of the energy conversion efficiency and, by inversely correcting the rate of change, computes the multiplication coefficients Kr, Kg, and Kb so that the luminance ratio among red, green, and blue is maintained constant. The thus computed coefficients are supplied to the respective multipliers 11 to 13.

For example, consider the case where the white balance is initially adjusted when the number of emissions is largest, and the white balance is corrected relative to its initial value for various values of the number of emissions; in that case, if the luminance of blue is taken as the reference since the blue phosphor has the shortest persistence (that is, the energy

09722661 112800

conversion efficiency decreases least), the luminance ratios of red, green, and blue, when plotted against the number of emissions, exhibit the characteristics shown in Figure 7. At this time, the change of the luminance ratio of green can be approximated by a linear equation $\alpha = (1-\alpha_0)/N_m \cdot N + \alpha_0$, where α is the luminance ratio with respect to the blue phosphor, α_0 is the luminance ratio when the number of emissions is zero, N is the number of emissions, and N_m is the maximum number of emissions.

To maintain the white balance constant regardless of the number of emissions, the rate of change of the luminance ratio should be inversely corrected; therefore, the multiplication coefficient K_g can be calculated as the reciprocal of the luminance ratio α , i.e., $K_g = 1/\alpha$.

The multiplication coefficient for red (R) can be calculated similarly. This of course applies if the color used as the reference is changed. In this way, by supplying the multiplication coefficients K_r , K_g , and K_b thus calculated by the microcomputer 2 to the respective multipliers 1 to adjust the signal amplitudes, the luminance ratio and, hence, the white balance can be maintained constant regardless of the number of emissions. In this example, the approximation is performed using a linear equation, but if the approximation is done using an equation of higher degree, a higher correction accuracy can be achieved.

In the present embodiment, first, to determine the characteristics of the phosphors, the relationship between the number of emissions and the luminance is measured, and the number of emissions versus luminance characteristics, such as shown in Figure 5A, is obtained. Then, from the measured data, the phosphor having the most linear characteristic (for example, the blue phosphor) is taken as the reference and, using this, the characteristics of the respective phosphors (red, green, and blue) are normalized and the luminance ratios are

computed for various values of the number of emissions.

More specifically, using the blue phosphor as the reference, the luminance ratio of each phosphor to the blue phosphor is computed. When the luminances of red, green, and blue at point A are denoted by L_r , L_g , and L_b , respectively, and the luminances at a given number of emissions by L_r , L_g , and L_b , respectively, then the normalized results are as shown below. Figure 7 shows the graphs (solid lines: red, green, and blue) plotted using the values calculated from the following equations.

$$\text{Luminance ratio of red to blue} = (L_r/L_r)/(L_b/L_b)$$

$$\text{Luminance ratio of green to blue} = (L_g/L_g)/(L_b/L_b)$$

To suppress the variation of the white balance due to changes in the number of emissions, the luminance ratio should be maintained constant regardless of the number of emissions. Therefore, the change of the luminance ratio is approximated by a linear equation (dashed line: green) as shown in Figure 7 and, using its reciprocal (multiplication coefficient K), the corresponding video signal is multiplied to correct the white balance. That is, the multiplication coefficient K is calculated using the equation $K = 1/\alpha = N_m/(N + \alpha_0(N_m - N))$.

Figure 8 is a diagram for explaining the multiplication coefficients for the three primary colors, red, green, and blue, used in the white balance correction circuit of Figure 6. The multiplication coefficients K_r , K_g , and K_b for red, green, and blue are plotted by calculating them from the equation $K = 1/\alpha = N_m/(N + \alpha_0(N_m - N))$. Here, reference character N represents the number of emissions, N_m the maximum number of emissions, and α_0 the luminance ratio at the minimum number of emissions.

The linear equation shown in Figure 7 is determined for each phosphor; that is, if the phosphor is determined, the equation for it is also determined.

00321T "T3322/60

Therefore, the equation for calculating its reciprocal (see Figure 8) is programmed in advance into the microcomputer 2, and the multiplication coefficients are calculated with various values of the number of emissions by using the programmed equation.

Figure 9 shows the results of the multiplications performed using the multiplication coefficients calculated by the microcomputer 2, that is, the luminance ratios of the three primary color phosphors corrected by the white balance correction circuit of Figure 6, plotted against the number of emissions. As is apparent from Figure 9, for all the phosphors of red, green, and blue (three primary colors) the luminance ratio can be maintained constant regardless of the number of emissions, and hence, correct white balance can be maintained regardless of the number of emissions.

More specifically, assume for example that the luminances of green and blue at the maximum number of emissions are 200 cd/m² and 80 cd/m², respectively, and the luminances at the minimum number of emissions are 60 cd/m² and 20 cd/m², respectively.

At this time, the luminance ratio of blue to green at the maximum number of emissions is

$$\text{Blue : Green} = 80 : 200 = 1 : 2.5$$

Likewise, the luminance ratio of blue to green at the minimum number of emissions is

$$\text{Blue : Green} = 20 : 60 = 1 : 3$$

The luminance ratio of green to blue is therefore 1.2 (3/2.5); since this value is α_0 , the multiplication coefficient K as its reciprocal is

$$K = 1/\alpha_0 = 1/1.2 = 0.83$$

That is, the green video signal (G) is corrected by multiplying its signal amplitude by 0.83. The red video signal (R) is also corrected in like manner. In this way, by calculating the multiplication coefficients with various values of the number of emissions by using the

corresponding to the display ratio used in the first embodiment, and based on the result of the detection, the microcomputer 2 calculates the multiplication coefficients. In the second embodiment, the number of emissions of each phosphor is controlled by the microcomputer 2 receiving the output of the current detection circuit 5 and controlling the number-of-emissions control circuit 7 so that the power consumption of the display apparatus is held below a predetermined value.

More specifically, the current detection circuit 5 detects the current being consumed by the panel drive circuit 6, and converts the current into a voltage value which is supplied to the microcomputer 2; based on the voltage value thus supplied, the microcomputer 2 reads the number of emissions from the number-of-emissions control circuit 7 and sets the number of emissions. Then, the microcomputer 2 computes the change of the luminance ratio due to the rate of change of the energy conversion efficiency corresponding to the thus set number of emissions, and calculates the multiplication coefficients K (K_r , K_g , and K_b) so that the luminance ratio among red, green, and blue is maintained constant. Using the multiplication coefficients K_r , K_g , and K_b , the multipliers 11, 12, and 13 multiply the respective video signals R, G, and B to adjust the amplitudes of the signals so that the white balance is maintained constant.

According to the second embodiment, the invention can be applied to a wide variety of display apparatuses including display apparatuses, such as CRTs, not equipped with an APL detection circuit.

Figure 12 is a block diagram showing a third embodiment of the white balance correction circuit according to the present invention. In Figure 12, reference numeral 8 is an address decoder, and 9 is a memory (read only memory - ROM).

As shown in Figure 12, the third embodiment differs

09722674.112800

from the first embodiment shown in Figure 6 in that the microcomputer 2 in the first embodiment is replaced by the address decoder 8 and ROM 9. In the ROM 9, the multiplication coefficients K_r , K_g , and K_b for the
5 respective video signals are stored for various values of APL (display ratio), and the multiplication coefficients appropriate to the APL detected by the APL detection circuit 3 are output from the ROM 9.

More specifically, the APL detection circuit 3
10 detects the APL of the input video signals and supplies the result to the address decoder 8, and the address decoder 8 generates the address in the ROM 9 at which the multiplication coefficients corresponding to the detected APL are stored. In the ROM 9, the multiplication
15 coefficients K_r , K_g , and K_b for correcting for the change of the luminance ratio due to the change in the energy conversion efficiency are prestored for various values of APL, that is, the number of emissions and, in accordance with the address supplied from the address decoder 8, the
20 corresponding multiplication coefficients are output and supplied to the respective multipliers 11, 12, and 13.

According to the third embodiment, the white balance can be corrected sufficiently even in cases where the number of emissions and the multiplication coefficients
25 K_r , K_g , and K_b cannot be approximated by simple equations (for example, when the energy conversion efficiency of each phosphor varies in a complex manner depending on the number of emissions).

In the third embodiment also, the APL detection
30 circuit 3 may be replaced by the current detection circuit 5, as in the second embodiment, and similar control can be performed by detecting the display current (the current consumption of the panel drive circuit 6) instead of the display ratio.

35 Figure 13 is a block diagram showing a fourth embodiment of the white balance correction circuit according to the present invention. In Figure 13,

09726621-11300

reference numeral 80 is an address decoder, and 91, 92, and 93 are ROMs (memories).

As shown in Figure 13, in the fourth embodiment, the ROM 9 and multipliers 11 to 13 in the third embodiment are replaced by ROMs 91 to 93; that is, the APL of the input video signals is detected by the APL detection circuit 3, and the detected value is converted by the address decoder 80 into the corresponding address in each of the ROMs 91 to 93. Data calculated by multiplying the respective video signals (R, G, and B) by given coefficients are prestored in the respective ROMs 91 to 93 to correct for the change of the luminance ratio due to the change in the energy conversion efficiency for various values of APL, that is, the number of emissions. Data stored in the respective ROMs 91, 92, and 93 are read out by using an address consisting, for example, of the address supplied from the address decoder 80 as the high-order bit address and each video signal as the low-order bit address, and based on the thus readout data, the amplitudes of the respective video signals are adjusted so that the luminance ratio among red, green, and blue is maintained constant.

According to the fourth embodiment, as in the third embodiment, the white balance can be corrected sufficiently even in cases where the number of emissions and the multiplication coefficients K_r , K_g , and K_b cannot be approximated by simple equations. Further, in the fourth embodiment also, the APL detection circuit 3 may be replaced by the current detection circuit 5, and similar control can be performed by detecting the display current instead of the display ratio.

Figure 14 is a block diagram showing a fifth embodiment of the white balance correction circuit according to the present invention.

As shown in Figure 14, a luminance-adjusting input from the outside (for example, the user) is supplied to the microcomputer 2 and, in accordance with this

09722621 112800

levels A to F of a plurality of input primary color video signals (for example, three primary color video signals R, G, and B) by different combinations of values of the number of emissions (processes P1 to P5, ...) as shown in
5 Figures 15 and 16. This techniques, as in the above-described embodiments, detects either the display ratio or display current of the image produced by the input video signals and, based on the detected display ratio or display current, performs driving control so that, for
10 example, the power consumption of the display apparatus as a whole does not exceed a predetermined value, while maintaining the gray levels A to F.

More specifically, when reference character F in Figures 15 and 16 represents 300 gray levels and C 150
15 gray levels, for example, if the display ratio of the image produced by the input video signals is high and there is a need to sufficiently reduce the power consumption in order to hold it below a specified value, the gray levels F and C are displayed using Ff (for
20 example, 150 sustain emission pulses) and Cf (for example, 75 sustain emission pulses), respectively, in the driving process P1 where the drive current is small (the number of emissions as a whole is small).
Conversely, if the display ratio of the image produced by
25 the input video signals is extremely low, for example, the gray levels F and C are displayed using Ff×5 (for example, 750 sustain emission pulses) and Cf×5 (for example, 375 sustain emission pulses), respectively, in the driving process P5 where the drive current is large
30 (the number of emissions as a whole is large). Similar processes are performed for other gray levels (A, B, ...). In this way, the display ratio (or the display current) of the image produced by the plurality of primary color video signals is detected, and the number
35 of emissions or the intensity is controlled for the plurality of primary color video signals in accordance

09722531 11300

with the detected display ratio (or display current).

As previously described, in the prior art white balance adjusting circuit, to adjust the white balance, a prescribed adjustment pattern (for example, a window pattern or the like) is displayed with specified gray levels, and the signal amplitudes of the respective color video signals R, G, and B are adjusted so that the desired white balance can be obtained. However, when the white balance is adjusted (for example, only once prior to shipment from the factory) by displaying a prescribed adjustment pattern with specified gray levels, the white balance will be shifted if the gray levels (input gray levels) change.

Figure 17 is a diagram showing the relationship between gray level and luminance ratio for each of the three primary color phosphors of red, green, and blue; the luminance ratio of each color at the maximum gray level, as measured relative to blue, is shown here. Further, Figure 18 is a block diagram showing a sixth embodiment of the white balance correction circuit according to the present invention, Figure 19 is a diagram for explaining the multiplication coefficients for the three primary colors, red, green, and blue, used in the white balance correction circuit of Figure 18, and Figure 20 is a diagram showing the relationship between gray level and luminance ratio for the three primary color phosphors when corrections are made by the white balance correction circuit of Figure 18.

As is apparent from a comparison between the previously given Figures 7 to 9 and the above Figures 16, 19, and 20, the relationship between the gray level (input gray level) and luminance ratio α of the three primary color phosphors in the sixth embodiment can be compared to the relationship between the number of emissions and the luminance ratio described in the first embodiment.

In Figure 18, reference numeral 11 to 13 are

multipliers, 2 is a microcomputer, 41 to 43 are γ -correction circuits, 101 is an input gray level detector, 102 is an address decoder, 103 is a memory (ROM), and 141 to 143 are multipliers (output gray level correctors).

5 The multipliers 11 to 13, the microcomputer 2, and the γ -correction circuits 41 to 43 are the same as those described in the prior art of Figure 4, and the description of these elements will not be repeated here.

As shown in Figure 18, in the white balance
10 adjusting circuit of the sixth embodiment, the input gray levels of the input video signals R, G, and B are detected (recognized) by the input gray level detector 101, and in accordance with the result of the detection, correction coefficients L_r , L_g , and L_b are output via the
15 address decoder 102 and memory 103. Each correction coefficient L has the relation $L = 1/\alpha$; hence, $L_r = 1/\alpha_r$, $L_g = 1/\alpha_g$, and $L_b = 1/\alpha_b$.

Using the input correction coefficients L_r and L_g (L_b), the multipliers 141 and 142 (143) apply corrections
20 in accordance with the following equation and calculate the output gray levels. In the equation, X is the input gray level, Y is the output gray level, and β is the maximum input gray level.

$$Y(X) = L + (1-L) \cdot (X/\beta)$$

25 Here, when the blue video signal is used as the reference (standard), since $L_b = 1/\alpha_b = 1/1 = 1$, there is no need to correct the input gray level of the blue video signal, and therefore, the multiplier 143 for the blue video signal need not be provided.

30 The sixth embodiment shown in Figure 18 is configured so that the correction coefficients L for the detected input gray levels are output from the memory 103; however, the circuit may be configured so that the correction coefficients L for the input gray levels are
35 computed using, for example, the microcomputer and the

00722621 " 142800

thus computed correction coefficients L are supplied to the respective multipliers (output gray level correctors) 141 to 143. Furthermore, the white balance correction circuit may be constructed using a microcomputer, etc.

5 which also perform white balance corrections by adjusting the amplitudes of the respective video signals in accordance with the number of emissions or the intensity of emission as previously described.

10 Figure 21 is a diagram showing the luminance characteristics of the three primary color phosphors when the sixth embodiment of the white balance correction circuit according to the present invention is applied, in comparison with those when it is not applied.

15 As is apparent from Figure 21, when the sixth embodiment of the white balance correction circuit is applied, it becomes possible to maintain correct white balance, regardless of the gray level, by adjusting, for example, the variation of the white balance due to the gray levels of the red, green, and blue phosphors in such
20 a manner that the luminance ratio is maintained constant.

Specific embodiments of the present invention have been described above by taking a plasma display apparatus as an example, but in other color display apparatuses (for example, CRTs, LED displays, etc.) using light
25 emitting elements whose persistence characteristics differ among red, green, and blue, white balance can likewise be corrected by applying the present invention without modification except that the number of emissions is replaced by the luminance (intensity) of emission.

30 As described above, according to the present invention, correct white balance can be maintained regardless of the number of emissions or the intensity of emission.

35 Many different embodiments of the present invention may be constructed without departing from the spirit and scope of the present invention, and it should be understood that the present invention is not limited to

0976661 11300

the specific embodiments described in this specification,
except as defined in the appended claims.

09/22/64 11:30